

LPR MVF LENS BULLET CAMERA

I6-320LPR-MVF1
I6-320LPR-MVF2



- 1/2.8" CMOS Sensor
- 2 Mega-Pixel
- True Day & Night (IR Cut Removable)
- H.265 (HEVC) Compression
- 0 Lux (IR On) Min. Illumination
- ONVIF
- True WDR
- 3D Noise Reduction
- Motion Detection and Privacy Masking
- AI Analytics (LPR)
- Audio Input + Output
- Alarm Input + Output
- 2.8-12mm / 7-22mm Motorized
- VF Lens with Auto Focus
- 60m IR Illumination
- PoE Support
- IP 67 Protection
- Micro SD Card Support
- Technician Port

Specifications

Camera	Model	I6-320IPE-MVF1	I6-320IPE-MVF2
		Video	Image Sensor
	Effective Pixels	1920x1080	
	Electronic Shutter	1/25s ~ 1/100000s	
	Frame Rate	1-25/30FPS	
	Day & Night	ICR	
	Min. Illumination	Day: 0.1lux / Night: 0.005lux (@F1.6, AGC On) 0lux with IR on	
	Audio	Audio compression	G.711A/G.711U
		Communication	Two-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
		Image Enhancement	True WDR (120dB), BLC, HLC, ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
		Motion Detection	Yes
		Analytics	LPR (Vehicle Speed of 0-70Km/h, 10000 Plate Database), Camera Tampering
	Compression	Video Compression	H.265S/H.264S*, H.265+/H.264+/H.265/H.264/MJPEG**
		Resolution	2MP / 1MP / D1 (704x576) / QVGA (480x240) / CIF (352x288)
		Multi-Stream	Master Stream: 2MP (1920x1080) / 1MP (1280x720) (1~30fps) Sub-Stream: 1MP/QVGA/D1/CIF Third Stream: QVGA/D1/CIF (1~30fps)
		Bit rate	64Kbps ~ 4Mbps@H.265 / 64Kbps ~ 6Mbps@H.264
		Encode Mode	VBR/CBR
		Image Quality	Five levels under VBR; Free adjustment under CBR

Housing	IR Distance	60m (4 High Power IR LED)	
	Lens (Field of View)	2.8-12mm MVF(103.4°-32.4°)	7-22mm MVF (44°-17.6°)
	Iris	DC Iris	
	Lens Mount	Ø14 Mount	
	Protection Rate	Water Proof: IP67	
	Bracket	3-Axis Wall Bracket	
Connectivity	Dimensions	279.5x88.9x100.3mm	
	Weight(gross)	~1040g	
	Network	RJ45 (+PoE)	
	Power	DC Socket	
	Analog Video Output	Technician Port	
	Audio Connectivity	Audio Input + Audio Output	
	SD Card	Event/Schedule based Main/Sub-Stream recording (Up to 128Gb)	
	Hard Reset Button	Yes	
	Alarm	Alarm in + Alarm Out	
	Network	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
User Access		Supports simultaneous monitoring for up to 3 users with multi-stream real time transmission	
Network Protocol		IPv4, IPv6, TCP, UDP, DHCP, NTP, DDNS, 802.1X, RTSP, Multicast, UPnP, Email, FTP, HTTPS, QoS	
ONVIF		Yes	
Others	Ethernet	100Mbps	
	PoE	Yes	
	Power Supply	DC12V/~910mA / PoE/~11W	
	Work Environment	-30°C~60°C, 10%~90% Humidity	

*Main Stream Only, **Sub-Streams Only

